ZÜCO LaCinta

EL 104 Swivel chair with armrests

SPECIFICATIONS

 Swivel chair with Syncro-Dynamic Advanced[®] mechanism, 2F- or 4F-multifunctional armrests, optipnal armrest pads covered in leather, designer backrest bracket in aluminum, medium-high, high or high nachrest with integrated neck support, fully upholstered

AREA OF USE

> Swivel chair for all office and conference areas

DESIGN

> Martin Ballendat

GUARANTEE

 > 5 years (operating life of 220 working days per year at 8 hours a day), in accordance with the guarantee conditions www.zueco.com/de-de/ infos/agb

CERTIFICATION/ STANDARDISATION

- > LGA (DIN EN 1335/1-3), GS safety seal
- > ISO 9001 (quality management system) since 1994
- > ISO 14001 (environmental management system) since 1997

TECHNICAL: SYNCRO-DYNAMIC ADVANCED®-MECHANISM

- Syncro-Dynamic Advanced[®] mechanism with constant backrest counterpressure and synchronised movement lockable in 4 positions
- > Seat-depth adjustment (5 cm) using sliding seat
- Integrated automatic seat-tilt adjustment (up to -4°) during the movement process thanks to a seat shell divided into three sections including active pelvic support
- Can be immediately and noticeably set to an individual bodyweight of approx. 40-125 kg
- > Seat-height adjustment (41-52 cm)

TRIMMING

- > Breathable moulded foam upholstery, CFC-free foamed to a hardness
- of 65 kg/m³ for the seat and 40 kg/ m³ for the back > Ergonomically shaped. Cushioned seat and backrest

		1	
	Description	Chair	Backrest
-	Foam thickness	3.5 cm	1.5 cm
	Foam density	65 kg/ m³	15 kg/ m³

non-bonded

non-bonded

BACKREST

Cover

- Back metal frame covered with elastic fabric, filled with PU foam and upholstered woth a textile or leather cover laminated with a synthetic fleece
- Back bracket made of polished die-cast aluminum

UPHOLSTERY FABRICS

 Several price categories with various upholstery qualities and colours may be selected (see current price list and colour cards)

MATERIALS

- > Diecast aluminium
- > Steel; ST 52 steel is used for high-stress parts, otherwise ST 37 is used
- Components have a powder-coated, chrome or black galvanised finish
 Polypropylene PP
- Polyurethane PU
- > Synthetic fleece 100 g
- > Needle fleece

SAFTEY GAS SPRING

> Standard: Chair height 41-53 cm (black standpipe)



CRUCIFORM BASE

> Standard: 5-ponted star cruciform in die-cast aluminum polished

CASTORS (Ø 65 MM)

- > Load-dependent restrained double castors
- > Standard: Hard castors for soft floors, black
- > Option at no extra charge: Soft castors for hard floors, black

ARMRESTS

- > Standard: 2F-armrests adjustable in height in black plastic
- > Option at an extra charge: 4F-multifunctional, polished aluminum
- > Height and width adjustable armrests PU soft (black)
- > Armrest bracket in black plastic
- Option at an extra charge: Leather pad
 Armrest bracket, polisehd aluminum

ECOLOGY

 All materials are manufactured in an environmentally friendly manner, are easily separable and recyclable

DIMENSIONS* (CM)

EL 104	Overall	Chair	Backrest
Height	122-134	41-53	79
Width	51/70	46	47
Depth	70	47-52	-

* All dimensions given are approximate.

WEIGHT

> Approx. 21 kg (with armrests)

SHIPPING METHOD

> Model is fully assembled and packed in film

RETURN

>Full return and recycling guarantee

