# **ZÜCO** LaCinta

## EL 0595 Executive swivel chair with armrests

## SPECIFICATIONS

 Executive swivel chair with armrests and high upholstered backrest with integrated neck support

## AREA OF USE

> Executive swivel chair for all office and conference areas

## DESIGN

Martin Ballendat

## GUARANTEE

> 5 years (operating life of 220 working days per year at 8 hours a day), in accordance with the guarantee conditions www.zueco.com/de-de/ infos/agb

## CERTIFICATION/ STANDARDISATION

- > LGA (DIN EN 1335/1-3), GS safety seal
- > ISO 9001 (quality management system) since 1994
- > ISO 14001 (environmental management system) since 1997

## TECHNICAL: SYNCRO-DYNAMIC ADVANCED®-MECHANISM

- Syncro-Dynamic Advanced® mechanism with constant backrest counterpressure and synchronised movement lockable in 4 positions
- > Seat-depth adjustment (5 cm) using sliding seat
- Integrated automatic seat-tilt adjustment (up to -4°) during the movement process thanks to a seat shell divided into three sections including active pelvic support
- Can be immediately and noticeably set to an individual bodyweight of approx. 40-125 kg
- > Seat-height adjustment (41-52 cm)

### TRIMMING

- Breathable moulded foam upholstery, CFC-free foamed to a hardness of 65 kg/m<sup>3</sup> for the seat and 40 kg/ m<sup>3</sup> for the back
- > Ergonomically shaped. Cushioned seat and backrest

Description	Chair	Backrest
Foam thickness	3.5 cm	1.5 cm
Foam density	65 kg/ m³	15 kg/ m³
Cover	non-bonded	non-bonded

## BACKREST

- Back metal frame covered with elastic fabric, filled with PU foam and upholstered woth a textile or leather cover laminated with a synthetic fleece
- > Back bracket made of polished die-cast aluminum

## UPHOLSTERY FABRICS

 Several price categories with various upholstery qualities and colours may be selected (see current price list and colour cards)

#### MATERIALS

- > Diecast aluminium
- > Steel; ST 52 steel is used for high-stress parts, otherwise ST 37 is used
- $\boldsymbol{\succ}$  Components have a powder-coated, chrome or black galvanised finish
- Polypropylene PP
- > Polyurethane PU
- > Synthetic fleece 100 g
- Needle fleece

## SAFTEY GAS SPRING

> Standard: Chair height 41-53 cm (black standpipe)



## CRUCIFORM BASE

> Standard: 5-ponted star cruciform in die-cast aluminum polished

# CASTORS (Ø 65 MM)

- > Load-dependent restrained double castors
- > Standard: Hard castors for soft floors, black
- > Option at no extra charge: Soft castors for hard floors, black

## ARMRESTS

- > Standard: 2F-armrests adjustable in height in black plastic
- > Option at an extra charge: 4F-multifunctional, polished aluminum
- > Height and width adjustable armrests PU soft (black)
- > Armrest bracket in black plastic
- Option at an extra charge: Leather pad
  Armrest bracket, polisehd aluminum

## ECOLOGY

 All materials are manufactured in an environmentally friendly manner, are easily separable and recyclable

## DIMENSIONS\* (CM)

EL 0595	Overall	Chair	Backrest
Height	126-138	41-53	85
Width	70	51	47
Depth	70	38-43	-

\* All dimensions given are approximate.

## WEIGHT

> Approx. 23,2 kg (with armrests)

## SHIPPING METHOD

> Model is fully assembled and packed in film

## RETURN

>Full return and recycling guarantee

